

U.S. Patent Application Serial No. 10/622,465
Amendment filed August 23, 2004
Reply to OA dated June 30, 2004

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

Claim 1 (canceled)

Claim 2 (currently amended): An apparatus for controlling a plurality of hydraulic motors and a clutch in which a single driving shaft is driven by outputs of a plurality of hydraulic motors, and one of the plurality of hydraulic motors drives the driving shaft through the clutch, comprising:

a first servo valve that controls the tilt rotation amount of a first hydraulic motor, and sets the tilt rotation amount of the first hydraulic motor to a zero tilt rotation amount when a zero fixing pressure, $P_{cs}=P_f$, of a predetermined value is input[[:]],

~~a clutch that~~ wherein the clutch is disengaged when a release pressure, P_k , of a predetermined value that is larger than the zero fixing pressure, P_f , of the predetermined value is input;

hydraulic vehicle speed detecting means for detecting a vehicle speed by a vehicle speed signal pressure, P_v , based on a vehicle speed; and

control valve means that releases an output command pressure, P_{cs} , to a return pressure, P_t , connected to a tank until a vehicle speed signal pressure, P_v , received from the hydraulic vehicle speed detecting means reaches a start pressure, P_b , of a predetermined value, and begins to output

U.S. Patent Application Serial No. 10/622,465
Amendment filed August 23, 2004
Reply to OA dated June 30, 2004

the command pressure, Pcs, to the first servo valve and the clutch when the vehicle speed signal pressure, Pv, exceeds ~~[[a]]~~ the start pressure, Pb, of the predetermined value.

Claim 3 (currently amended): An apparatus for controlling a plurality of hydraulic motors and a clutch according to claim 2, further comprising:

a zero tilt rotation detecting valve that detects the tilt rotation amount of the first hydraulic motor, and causes a command pressure, Pcs, to be in communication with the clutch to disengage the clutch when the zero tilt rotation amount is detected~~[[; and]]~~, wherein the

~~control valve means that releases an output command pressure, Pcs, to a return pressure, Pt, connected to a tank until a vehicle speed signal pressure, Pv, received from the hydraulic vehicle speed detecting means reaches a start pressure, Pb, of a predetermined value, and begins to output the command pressure, Pcs, to the first servo valve and the zero tilt rotation detecting valve when the vehicle speed signal pressure, Pv, exceeds~~ [[a]] the start pressure, Pb, of the predetermined value.

Claim 4 (canceled)